

	XDCAM HD422 50 Mbps encapsulated MXF OP1a or QuickTime
Video	• 1920x1080
	Constant 29.97 frames/sec interlaced, upper filed first
	Safe title zone: 90% height and width of the full HD picture
Audio	PCM, 48kHz, 24-bit, -2dBTP Max. PCM, 48kHz, 24-bit, -2dBTP Max.
	An audio mix ranging between 2 tracks (stereo) and to 6 tracks (5.1)
	Track allocation: 1:L2:R3:C4:LFE5:Ls6:Rs7:Lt/Lo8:Rt/Ro or stereo mix on tracks 1-2 and 7-8
	 Integrated commercial loudness: -24LKFS +/-2LU (measured using UIT-R BS.1770-3 algorithm)
Lip sync	1 field maximum tolerable sound and picture misalignment
Time code	Drop frame mode, continuous (from start to end – not visible on screen)
	• Start at 10;00;00;00
	No lead-in/lead-out, advertising only
Close captioning (CC)	All commercials must be closed captioned (.scc files or embedded into video file)
	(required by the CRTC).
	Commercials with no voice over, with music only, still require closed captioning: meaning
	a musical note ♪ or the word "music"
	must appear in the closed captioning throughout the commercial. The leasth of the CC file must be the correspond to leasth of the cides file. The corresponding to the commercial contraction.
	The length of the CC file must be the same as the length of the video file. The same The length of the code.
	 applies to the time code The CC file needs to be structured for 29.9fps, Type: drop frame
	The CC file fleeds to be structured for 29.91ps, Type: drop frame



CONTENT SPECIFICATIONS

VO

Audio of the commercial.

SUPER/VISUAL

Inside the frame:

· Advertiser's commercial message.

- On the frame :
 Télé-Québec's branding.
- · Countdown to zero.
- Name of upcoming program.